

Motorbike 4T Shooter

Description

Increases engine performance. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents renewed formation. This also reduces fuel consumption. Protects the entire fuel system from corrosion. Prevents carburetor icing. Cat tested.

Properties

- good corrosion protection
- environmentally friendly
- for carburetor and fuel-injection engines
- tested for catalytic converters
- reduces residues
- optimizes engine performance
- normalizes gasoline consumption and exhaust emissions values
- highly economical
- increases operational reliability

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>142 °F
Pour point	-49 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 104 °F	<7 mm ² /s
Density at 59 °F	0,765 g/cm ³

Areas of application

Add to fuel in all 4-cycle engines (carburetor and injection system). 80 ml sufficient for 1.3 - 2.6 gal (5 - 10 l) fuel. Add every time you fill up.

Application

Add to the fuel tank. For the optimum effect, add every time you refuel. Fully compatible with all gasoline grades. 80 ml is sufficient for 1.3 - 2.6 gal (5 - 10 l) of fuel.



Available pack sizes

80 ml Can sheet metal	20142
	GB-F-USA-CAN

Our information is based on thorough research and may be considered reliable, although not legally binding.