Product information

PI 21/09/01/2018

LIQUI MOLY

Motorbike Fork Oil SAE 5W light

Description

Full synthetic fork oil and shock-absorber oil. Reduces shear losses and provides sure handling performance even after long use. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- lasting corrosion protection
- prevents foam formation
- increases driving safety
- high wear resistance
- prevents seals from swelling

Technical data

Density at 59 °F 0,825 g/cm³

DIN 51757

Viscosity at 104 °F 18,0 mm²/s

ASTM D 7042-04

Viscosity at 212°F 4,1 mm²/s

ASTM D 7042-04

Viscosity index 131

DIN ISO 2909

Pour point -98 °F

DIN ISO 3016

Flash point 428 °F

DIN ISO 2592

Color number (ASTM) L 0,5

DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheel vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.



Available pack sizes

1 l Can plastic 20094

GB-F-E-USA-CAN

Our information is based on thorough research and may be considered reliable, although not legally binding.