

Motorbike Gear Oil SAE 75W-140 (GL5) VS

Description

High-performance high-pressure transmission oil made from high-grade synthetic base oils and additives. Facilitates smooth and precise shifting even under extreme conditions and complies with performance class API GL5. Has excellent wear protection properties and ideal viscosity-temperature behavior.



Properties

- outstanding corrosion protection
- reduces transmission noise
- excellent wear resistance
- wide viscosity range

Available pack sizes

1 l Can plastic 20088
GB-F-E-USA-CAN

Specifications and approvals:

API GL5 LS

Our information is based on thorough research and may be considered reliable, although not legally binding.

Technical data

SAE class (gear oils)	75W-140 SAE J306
Density at 59 °F	0,870 g/cm ³ DIN 51757
Viscosity at 104 °F	179 mm ² /s ASTM D 7042-04
Viscosity at 212°F	25,0 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	172 DIN ISO 2909
Pour point	-60 °F DIN ISO 3016
Flash point	406 °F DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Areas of application

For motorcycle transmissions and final drives operated under the highest load. Observe the instructions of the transmission manufacturer.

Application

The transmission manufacturer's instructions must be followed. Mixable with mineral-base oil residues which can remain during oil changes in transmissions and drives. Optimum effect only when used alone. Can be easily disposed of with standard used oil.